



Cutter Limitations for :

Standard/Extended Chimney

Cutter Size	Maximum Wall	DR 7		DR 9		DR 11		DR 17		Hex.	Standard	360 Brass
		IPS	DIPS	IPS	DIPS	IPS	DIPS	IPS	DIPS		Part Number	Part Number
0.250	0.725	3"	N/A	4"	4"	6"	4"	8"	8"	1/2"	1047819	N/A
0.500	0.675	3"	N/A	4"	4"	4"	4"	8"	8"		1047818	
0.500 XL	1.007	4"	4"	6"	6"	8"	8"	14"	12"		1047820	
0.800	0.670	3"	N/A	4"	4"	4"	4"	8"	8"		1047817	1047772
0.800 XL	0.859	4"	4"	4"	4"	6"	6"	10"	10"		1047831	1047693
0.800 XXL*	1.505	8"	6"	10"	10"	12"	12"	20"	18"		1047777	1047776
1.000 XL	1.300	6"	6"	8"	8"	10"	10"	16"	16"		1047698	N/A
1.000 XXL*	1.805	8"	8"	12"	12"	16"	14"	24"	20"		1047692	1047816

* Cannot be used on 2" mains or smaller

High Volume Tapping Tees

Cutter Size	Maximum Wall	DR 7		DR 9		DR 11		DR 17		Hex.	Standard	360 Brass
		IPS	DIPS	IPS	DIPS	IPS	DIPS	IPS	DIPS		Part Number	Part Number
1.500 ^A	0.410	2"	N/A	2"	N/A	3"	N/A	4"	N/A	5/8"	1047812	N/A
1.880	1.410	6"	6"	8"	8"	12"	10"	18"	18"		1047811	
1.880 XL	1.650	8"	8"	10"	10"	14"	12"	20"	20"		1047813	1047814

^A Cutter used for 2" mains ONLY

*DriscoPlex[®] tapping tees and cutters are designed and intended to tap polyethylene mains of wall thickness as defined herein. Special precautions are necessary when working in gaseous environments or elevated temperatures. Consult your Operations and Safety Manuals for specific recommendations. The use of these tapping tees and cutters beyond this scope is at the user's own risk.