



## Socket Coupling

PRODUCED TO ASTM D2513 and D2683

<u>Socket Coupling</u>	<u>Dimensions G x E (in)</u>	<u>Package Quantity</u>	<u>Package Weight (lbs.)</u>	<u>Box Quantity</u>	<u>CSA<sup>1</sup></u>	<u>IAPMO</u>	<u>Reference Number</u>
1/2" CTS	2.30 x 1.07	10	0.5	100	x	x	*M.50*CPLG*
3/4" CTS	2.10 x 1.27		0.5	50	x		*M.75*CPLG*
1" CTS	1.95 x 1.52		0.7	50	x		*M010*CPLG*
1 1/4" CTS	1.54 x 1.80		0.6	50	x		*M1.25*CPLG*
1/2" IPS	2.10 x 1.27		0.5	50	x		*M.50*CPLG*
3/4" IPS	1.95 x 1.46		1.0	50	x	x	*M.75*CPLG*
1" IPS	1.54 x 1.80		0.7	50	x	x	*M010*CPLG*
1 1/4" IPS	2.08 x 2.32		1.6	20	x	x	*M1.25*CPLG*
1 1/2" IPS	2.33 x 2.65		2.2	50	x	x	*M1.50*CPLG*
2" IPS	2.36 x 3.31		3.6	40	x	x	*M020*CPLG*
3" IPS	2.85 x 4.88		9.2	10	x	x	*M030*CPLG*
4" IPS	3.11 x 6.30		17.6	10	x	x	*M040*CPLG*

<sup>1</sup> - CSA and IAPMO available as DriscoPlex<sup>®</sup> 6500 MDPE materials ONLY.

x - Indicates certification/approval for application or test at additional charge.

- Drawing No. - CU70B254