

ULTRALINE® HDPE WATER SERVICE PIPE & TUBING

DRISCOPEX® 5100 SERIES ULTRALINE® HDPE WATER SERVICE PIPE & TUBING *Now With Higher Pressure Ratings!*



Ultraline® HDPE Water Service Pipe and Tubing is available to meet your needs in compliance with ASTM D2239, ASTM D2737, or ASTM D3035 product standard.

Produced from only the highest rated HDPE pipe materials, Driscoplex® 5100 Series Ultraline® HDPE Pipe and Tubing are PE4710 pipe materials listed in PPI-TR4.

Ultraline® HDPE Water Service Pipe and Tubing from Performance Pipe meets the requirements of:

- AWWA C901-08
- NSF 61
- NSF 14

When Performance Matters Rely on
Performance Pipe

ULTRALINE® HDPE WATER SERVICE PIPE & TUBING

Performance Pipe Ultraline® Water Service Pipe and Tubing is intended for applications to 80°F, contact Performance Pipe for guidance on operating at higher temperatures.


ASTM D2239 Inside Diameter Controlled HDPE Pipe (IPS / SIDR)

SIZE	SIDR	NOMINAL OD / ID	COIL LENGTH / PALLET QTY	COIL LENGTH / PALLET QTY	WEIGHT LB/100FT	PRESSURE CLASS
3 / 4 "	7	1.074 / .824	100' / 1800'	400' / 4000'	16	250 psi
1"	7	1.367 / 1.049	100' / 1800'	300' / 2400'	25	250 psi
1 - 1 / 4 "	7	1.798 / 1.380	100' / 1500'	300' / 2100'	43	250 psi
1 - 1 / 2 "	7	2.098 / 1.610	100' / 1400'	300' / 1800'	59	250 psi
2 "	7	2.692 / 2.067	100' / 1000'	300' / 2100'	97	250 psi

ASTM D2737 Outside Diameter Controlled HDPE Tubing (CTS)

SIZE	SDR	NOMINAL OD / ID	COIL LENGTH / PALLET QTY	COIL LENGTH / PALLET QTY	WEIGHT LB/100FT	PRESSURE CLASS
3 / 4 "	9	0.875 / 0.669	100' / 1800'	500' / 7500'	10	250 psi
1"	9	1.125 / 0.860	100' / 1600'	300' / 4200'	17	250 psi
1 - 1 / 4 "	9	1.375 / 1.051	100' / 1400'	300' / 2400'	26	250 psi
1 - 1 / 2 "	9	1.625 / 1.241	100' / 1300'	300' / 2400'	36	250 psi
2 "	9	2.125 / 1.625	100' / 1300'	300' / 2700'	61	250 psi

ASTM D3035 Outside Diameter Controlled HDPE Pipe (IPS/SDR)



SIZE	SDR	NOMINAL OD / ID	COIL LENGTH / PALLET QTY	COIL LENGTH / PALLET QTY	WEIGHT LB/100FT	PRESSURE CLASS
3 / 4 "	11	1.050"/0.849"	150' / 1800'	500' / 3500'	13	200 psi
1"	11	1.315"/1.061"	150' / 1800'	500' / 3000'	20	200 psi
1-1/4"	11	1.660"/1.358"	150' / 1500'	500' / 6000'	31	200 psi
1-1/2"	11	1.900"/1.554"	250' / 2500'	500' / 4000'	41	200 psi
2"	13.5	2.375"/2.002"	150' / 1800'	500' / 3500'	53	160 psi
2"	11	2.375"/1.917"	150' / 1800'	500' / 3500'	64	200 psi
3"	17	3.500"/3.063"	250' / 1750'	1000' / 2000'	94	125 psi
3"	13.5	3.500"/2.951"	250' / 1750'	1000' / 2000'	116	160 psi
3"	11	3.500"/2.826"	250' / 1750'	1000' / 2000'	140	200 psi

Solid Black pipe and tubing is standard. Blue Striped pipe and tubing is available.

Contact your Performance Pipe representative for additional sizes and information.

When Performance Matters Rely on
Performance Pipe